

ROOT® PAR IP

LED OUTDOOR SPOTLIGHT



FEATURES

- ▶ Robust LED light with 7× RGBW LEDs for versatile outdoor applications
- ▶ Flexible positioning thanks to swivelling foot for easy adjustment of the beam angle, without additional brackets
- ▶ 3000 lumens and a beam angle of 36°
- ▶ True1-compatible power sockets and three-pin XLR connectors for easy integration into existing DMX set-ups
- ▶ Patented EZchase® DMX delay function for creative chaser effects and colour changes without much programming effort
- ▶ Compact, lightweight design weighing only 4 kg for easy handling and transport
- ▶ IP65 protection class for safe use at outdoor events, even in difficult weather conditions

DESCRIPTION

Thanks to its robust design and IP65 protection class, the Cameo ROOT® PAR IP is a versatile LED light that is particularly suitable for use at outdoor events. Equipped with 7× RGBW LEDs, it delivers a solid light output of 3000 lumens and a beam angle of 36°, making it a reliable choice for many applications.

The integrated tilt foot mechanism is a practical feature. The tilt angle of the ROOT® PAR IP can be easily adjusted without additional brackets, allowing flexible positioning. This makes the luminaire ideal for a wide variety of lighting situations – whether for direct illumination on stage or for accent lighting on facades and in outdoor areas.

The ROOT® PAR IP is easy to operate: with True1-compatible power sockets and three-pin XLR connections for DMX control, it can be easily integrated into existing set-ups. The EZchase® DMX delay function also makes it possible to implement simple chaser patterns and colour changes without a great deal of programming effort.

Its compact design and low weight of 4 kg don't only make the ROOT® PAR IP easy to transport but also quickly ready for use – a reliable solution for various outdoor lighting projects.



Features and specifications
subject to change without notice.

adamhall.com

ROOT® PAR IP

LED OUTDOOR SPOTLIGHT



SPECIFICATIONS

| | |
|---------------------------------------|---|
| Item number: | CLROOTPARIP |
| Photometric values | |
| Illuminant type | LED RGBW |
| Luminous flux | 3000 lm |
| Exchangable lens | No |
| Exchangable optics | No |
| Beam/Field angle | 19° / 33° |
| Dimmer resolution | 16 Bit |
| Colours | |
| LED colours | Red, Green, Blue, White |
| Halogen simulation redshift/DTW | No |
| Colour rendering index (CRI) | > 66 |
| Effects | |
| Strobe | 0 -20 Hz |
| Iris | No |
| Animation | No |
| Framing blades | No |
| Control | |
| Controller protocols | DMX512 |
| Number of DMX control modes | 12 |
| Stand alone operating modes | Sound controlled, Autorun, Master/slave, Static, Endless loop |
| Data in connector | XLR 3-pole male |
| Data out connector | XLR 3-pole female |
| Mains operation | |
| Operation voltage | 100 V AC - 240 V AC / 50 -60 Hz |
| Rated power | 65 |
| Mains connector | Mains plug device male IP65 |
| Housing | |
| Chassis material | Die-cast aluminium |
| Colour | Black |
| Environmental | |
| Protection class | IP65 |
| Ambient temperature | -15 – 40 °C |
| Maximum air humidity (non-condensing) | 100 % |
| Dimensions & weight | |
| Width | 272 mm |
| Height | 242 mm |
| Depth | 166 mm |
| Weight | 4.2 kg |