

S4 IP

LED SOFTLIGHT PANEL - IP65
DMX CONTROL TABLE



1Ch Dim (User colour 1)	2Ch Dim 16bit (User colour 1)	2Ch CCT	4Ch CCT	Function	Values			
1	1	1	1	Dimmer	000	-	255	0% to 100%
	2		2	Dimmer fine	000	-	255	0% to 100%
		2	3	CCT	000	-	006	Warm white
					007	-	046	Warm white -> 2700k
					047	-	047	Bulb white (2700k)
					048	-	087	2700k -> 3200k
					088	-	088	Halogen white (3200k)
					089	-	128	3200k -> 4000k
					129	-	129	Neutral white (4000k)
					130	-	169	4000k -> 5600k
					170	-	170	Studio white (5600k)
					171	-	210	5600k -> 6500k
					211	-	211	Daylight white (6500k)
					212	-	251	6500k -> cold Daylight
					252	-	255	Cold daylight
			4	Tint (affects colour temperature)	000	-	000	Off
		001			-	127	Magenta -> neutral	
		128			-	128	Neutral	
		129			-	255	Neutral -> green	

S4 IP

LED SOFTLIGHT PANEL - IP65
DMX CONTROL TABLE



3Ch RGB (calibrated)	4Ch RGBW (raw)	8Ch RGBW 16Bit	Function	Values			
1	1	1	Red	000	-	255	0% to 100%
		2	Red fine	000	-	255	0% to 100%
2	2	3	Green	000	-	255	0% to 100%
		4	Green fine	000	-	255	0% to 100%
3	3	5	Blue	000	-	255	0% to 100%
		6	Blue fine	000	-	255	0% to 100%
	4	7	White	000	-	255	0% to 100%
		8	White fine	000	-	255	0% to 100%

6Ch HSI-CCT	7Ch RGB CCT	Function	Values				Sub-Group
1	1	Dimmer	000	-	255	0% to 100%	Dimmer
2		Dimmer fine	000	-	255	0% to 100%	
	2	Red	000	-	255	0% to 100%	Red
	3	Green	000	-	255	0% to 100%	Green
	4	Blue	000	-	255	0% to 100%	Blue
3		Hue	000	-	255	0° (red) thru 360°	HSI
4		Saturation	000	-	255	from 0% (white) to 100% pure Colour	
5	6	Colour Temperature (affects RGB and HSI)	000	-	005	No function	CCT
			006	-	006	Warm white	
			007	-	046	Warm white -> 2700K	
			047	-	047	Bulb White (2700K)	
			048	-	087	2700K -> 3200K	
			088	-	088	Halogen White (3200K)	
			089	-	128	3200K -> 4000K	
			129	-	129	Neutral White (4000K)	
			130	-	169	4000K -> 5600K	
			170	-	170	Studio White (5600K)	
			171	-	210	5600K -> 6500K	
			211	-	211	Daylight White (6500K)	
			212	-	251	6500K -> Cold Daylight	
252	-	255	Cold Daylight				
6	7	Tint (affects Colour Temperature)	000	-	000	Off	Tint
			001	-	127	Magenta -> neutral	
			128	-	128	Neutral	
			129	-	255	Neutral -> green	

S4 IP

LED SOFTLIGHT PANEL - IP65
DMX CONTROL TABLE



6Ch x y	Function	Values			
1	Dimmer	000	-	255	0% to 100%
2	Dimmer fine	000	-	255	0% to 100%
3	x	000	-	255	0.0000 - 0.8000
4	x fine	000	-	255	
5	y	000	-	255	0.0000 - 0.8000
6	y fine	000	-	255	

7Ch Direct Control	10Ch Direct CCT	Function	Values				Sub-Group
1	1	Dimmer	000	-	255	0% to 100%	Dimmer
2	2	Dimmer fine	000	-	255	0% to 100%	
	3	Strobe func- tions	000	-	005	Strobe open	Multifunctional Strobe
			006	-	010	Strobe closed	
			011	-	022	Ramp up/down, slow -> fast	
			023	-	033	Ramp up/down random, slow->fast	
			034	-	045	Ramp up, slow -> fast	
			046	-	056	Ramp up random, slow -> fast	
			057	-	068	Ramp down, slow -> fast	
			069	-	079	Ramp down random, slow -> fast	
			080	-	102	Random Strobe effect, slow -> fast	
			103	-	127	Strobe Break effect, 5s.1s (short burst with break)	
			128	-	250	Strobe slow -> fast <1Hz - 20Hz	
	251	-	255	Strobe open			
3	4	Red	000	-	255	0% to 100%	RGBW
4	5	Green	000	-	255	0% to 100%	
5	6	Blue	000	-	255	0% to 100%	
6	7	White	000	-	255	0% to 100%	

S4 IP

LED SOFTLIGHT PANEL - IP65 DMX CONTROL TABLE



8	Colour Temperature (affects RGBW)	000	-	005	No function	CCT	
		006	-	006	Warm white		
		007	-	046	Warm white -> 2700K		
		047	-	047	Bulb White (2700K)		
		048	-	087	2700K -> 3200K		
		088	-	088	Halogen White (3200K)		
		089	-	128	3200K -> 4000K		
		129	-	129	Neutral White (4000K)		
		130	-	169	4000K -> 5600K		
		170	-	170	Studio White (5600K)		
		171	-	210	5600K -> 6500K		
		211	-	211	Daylight White (6500K)		
		212	-	251	6500K -> Cold Daylight		
		252	-	255	Cold Daylight		
9	Tint (affects Colour Temperature)	000	-	000	Off	Tint	
		001	-	127	Magenta -> neutral		
		128	-	128	Neutral		
		129	-	255	Neutral -> green		
7	10	Device Settings (please read remark 1*)	000	-	024	No function	Device Settings
			025	-	025	Record User Colour 1 (hold 3s)	
			026	-	026	Record User Colour 2 (hold 3s)	
			027	-	027	Record User Colour 3 (hold 3s)	
			028	-	028	Record User Colour 4 (hold 3s)	
			029	-	029	Record User Colour 5 (hold 3s)	
			030	-	030	Record User Colour 6 (hold 3s)	
			031	-	031	Record User Colour 7 (hold 3s)	
			032	-	032	Record User Colour 8 (hold 3s)	
			033	-	073	No function	
			074	-	075	Dimmer Response LED (hold 3s)	
			076	-	077	Dimmer Response Halogen (hold 3s)	
			078	-	081	No function	
			082	-	083	DTW (Red-Shift) on (hold 1,5 s)	

S4 IP

LED SOFTLIGHT PANEL - IP65 DMX CONTROL TABLE



7	10	Device Settings (please read remark 1*)	084	-	085	DTW (Red-Shift) off (hold 1,5 s)	Device Settings
			086	-	097	No function	
			098	-	099	Auto Fan (hold 3s)	
			100	-	101	Fan Off (hold 3s)	
			102	-	103	Fan Constant Low (hold 3s)	
			104	-	105	Fan Constant Medium (hold 3s)	
			106	-	107	Fan Constant High (hold 3s)	
			108	-	119	No function	
			120	-	121	PWM 1 (650 Hz) (hold 3s)	
			122	-	123	PWM 2 (1530 Hz)(hold 3s)	
			124	-	125	PWM 3 (3600 Hz)(hold 3s)	
			126	-	127	PWM 4 (12 kHz)(hold 3s)	
			128	-	129	PWM 5 (18,9 kHz)(hold 3s)	
			130	-	131	PWM 6 (25 kHz)(hold 3s)	
			132	-	133	RAW (hold 3s)	
			134	-	135	Calibrated (hold 3s)	
			136	-	137	User Calibrated (hold 3s)	
			138	-	139	Smart Calibration (hold 3s)	
			140	-	141	Display on (hold 3s)	
			142	-	143	Display off (hold 3s)	
			144	-	163	No function	
			164	-	165	Dimmer Curve Linear (hold 3s)	
			166	-	167	Dimmer Curve Exponential (hold 3s)	
			168	-	169	Dimmer Curve Logarithmic (hold 3s)	
			170	-	171	Dimmer Curve S-Curve (hold 3s)	
			172	-	239	No function	
240	-	241	Default set (except DMX-Address, DMX-Mode) (hold 3s)				
242	-	243	Default set (except DMX-Address, DMX-Mode and User Colour/Loops) (hold 3s)				
244	-	255	No function				

S4 IP

LED SOFTLIGHT PANEL - IP65
DMX CONTROL TABLE



16Ch Direct CCT	18 Ch Full Access	Function	Values				Sub-Group
1	1	Dimmer	000	-	255	0% to 100%	Dimmer
2	2	Dimmer fine	000	-	255	0% to 100%	
3	3	Strobe func- tions	000	-	005	Strobe open	Multifunctional Strobe
			006	-	010	Strobe closed	
			011	-	022	Ramp up/down, slow -> fast	
			023	-	033	Ramp up/down random, slow->fast	
			034	-	045	Ramp up, slow -> fast	
			046	-	056	Ramp up random, slow -> fast	
			057	-	068	Ramp down, slow -> fast	
			069	-	079	Ramp down random, slow -> fast	
			080	-	102	Random Strobe effect, slow -> fast	
			103	-	127	Strobe Break effect, 5s.....1s (short burst with break)	
			128	-	250	Strobe slow -> fast <1Hz - 20Hz	
251	-	255	Strobe open				
4	4	Red	000	-	255	0% to 100%	Red
5	5	Red fine	000	-	255	0% to 100%	
6	6	Green	000	-	255	0% to 100%	Green
7	7	Green fine	000	-	255	0% to 100%	
8	8	Blue	000	-	255	0% to 100%	Blue
9	9	Blue fine	000	-	255	0% to 100%	
10	10	White	000	-	255	0% to 100%	White
11	11	White fine	000	-	255	0% to 100%	
12	12	Colour Tempe- rature (affects RGB)	000	-	005	No function	CCT
			006	-	006	Warm white	
			007	-	046	Warm white -> 2700K	
			047	-	047	Bulb White (2700K)	
			048	-	087	2700K -> 3200K	
			088	-	088	Halogen White (3200K)	
			089	-	128	3200K -> 4000K	
			129	-	129	Neutral White (4000K)	
			130	-	169	4000K -> 5600K	
			170	-	170	Studio White (5600K)	
			171	-	210	5600K -> 6500K	
			211	-	211	Daylight White (6500K)	
			212	-	251	6500K -> Cold Daylight	
			252	-	255	Cold Daylight	

Cameo®

is a registered brand of the Adam Hall Group.

Phone: +49 60 81 - 94 19-0

adamhall.com

S4 IP

LED SOFTLIGHT PANEL - IP65
DMX CONTROL TABLE



13	13	Tint (affects Colour Temperature)	000	-	000	Off	Tint
			001	-	127	Magenta -> Neutral	
			128	-	128	neutral	
			129	-	255	Neutral -> Green	

S4 IP

LED SOFTLIGHT PANEL - IP65 DMX CONTROL TABLE



			Lee Filter No.	
		000 - 005	no function	
		006 - 009	46 Dark Magenta	
		010 - 013	29 Plasa Red	
		014 - 017	26 Bright Red	
		018 - 021	127 Smokey Pink	
		022 - 025	36 Medium Pink	
		026 - 029	19 Fire	
		030 - 033	135 Deep Golden Amber	
		034 - 037	778 Millennium Gold	
		038 - 041	21 Gold Amber	
		042 - 045	157 Pink	
		046 - 049	110 Middle Rose	
		050 - 053	109 Light Salmon	
		054 - 057	35 Light Pink	
		058 - 061	134 Golden Amber	
		062 - 065	17 Surprise Peach	
		066 - 069	746 Brown	
		070 - 073	105 Orange	
		074 - 077	20 Medium Amber	
		078 - 081	768 Egg Yolk Yellow	
		082 - 085	15 Deep Straw	
		086 - 089	767 Oklahoma Yellow	
		090 - 093	101 Yellow	
		094 - 097	100 Spring Yellow	
		098 - 101	88 Lime Green	
		102 - 105	121 LEE Green	
		106 - 109	738 Jas Green	
		110 - 113	89 Moss Green	
		114 - 117	139 Primary Green	
		118 - 121	124 Dark Green	
		122 - 125	323 Jade	
		126 - 129	354 Special Steel Blue	
		130 - 133	116 Medium Blue-Green	
		134 - 137	183 Moonlight Blue	
		138 - 141	132 Medium Blue	
		142 - 145	119 Dark Blue	
		146 - 149	716 Mikkell Blue	
		150 - 153	71 Tokyo Blue	
		154 - 157	181 Congo Blue	
		158 - 161	799 Special KH Lavender	
		162 - 165	707 Ultimate Violet	

14

14

Colour Presets
(override RGBW,
Colour Temperature)

Colour Presets

S4 IP

LED SOFTLIGHT PANEL - IP65
DMX CONTROL TABLE



Roscolux Filter No.
46
26
50
36
19
22
21
38
331
35
321
17
15
20
15
313
312
10
388
86
4460
89
90
393
370
95
77
74
384
382
382
382

Cameo®
is a registered brand of the Adam Hall Group.

Adam Hall GmbH | Adam-Hall-Str. 1
61267 Neu-Anspach | Germany

Phone: +49 60 81 · 94 19-0
adamhall.com

S4 IP

LED SOFTLIGHT PANEL - IP65 DMX CONTROL TABLE



14	14	Colour Presets (override RGBW, Colour Temperature)	166 - 169	343 Special Medium Lavender	Colour Presets
			170 - 173	798 Chrysalis Pink	
			174 - 177	701 Provence	
			178 - 181	797 Deep Purple	
			182 - 185	48 Rose Purple	
			186 - 189	345 Fuchsia Pink	
			190 - 193	795 Magical Magenta	
			194 - 197	128 Bright Pink	
			198 - 201	2 Rose Pink	
			202 - 207	User Colour_1	
			208 - 213	User Colour_2	
			214 - 219	User Colour_3	
			220 - 225	User Colour_4	
			226 - 231	User Colour_5	
			232 - 237	User Colour_6	
238 - 243	User Colour_7				
244 - 249	User Colour_8				
250 - 255	no function				
15	15	Colour Preset Crossfade (Affects Colour Temperature, HSI too)	000 - 005	0s	Colour Presets
			006 - 105	0,1s - 10s (0,1s Steps)	
			106 - 214	11s - 119s (1s Steps)	
			215 - 244	2m - 4m50s (10s Steps)	
			245 - 255	5m - 15m (1m Steps)	
	16	Effect Macro	000 - 005	No Function	Light simulation
			006 - 039	Colour Chase	
			040 - 068	Police Car	
			069 - 096	Firetruck	
			097 - 125	Fire	
			126 - 154	Clouds	
			155 - 182	Fireworks	
			183 - 211	Paparazzi	
			212 - 240	Lightning	
			241 - 255	No Function	
	17	Effect Macro Speed	000 - 255	Effect Macro speed slow --> fast	
16	18	Device Settings (please read remark 1*)	000 - 024	No function	Device Settings
			025 - 025	Record User Colour 1 (hold 3s)	
			026 - 026	Record User Colour 2 (hold 3s)	

S4 IP

LED SOFTLIGHT PANEL - IP65
DMX CONTROL TABLE



357
358
358
347
48
346
339
44

S4 IP

LED SOFTLIGHT PANEL - IP65 DMX CONTROL TABLE



16	18	Device Settings (please read remark 1*)	027	-	027	Record User Colour 3 (hold 3s)	Device Settings
			028	-	028	Record User Colour 4 (hold 3s)	
			029	-	029	Record User Colour 5 (hold 3s)	
			030	-	030	Record User Colour 6 (hold 3s)	
			031	-	031	Record User Colour 7 (hold 3s)	
			032	-	032	Record User Colour 8 (hold 3s)	
			033	-	073	No function	
			074	-	075	Dimmer Response LED (hold 3s)	
			076	-	077	Dimmer Response Halogen (hold 3s)	
			078	-	081	No function	
			082	-	083	DTW (Redshift) on (hold 1,5 s)	
			084	-	085	DTW (Redshift) off (hold 1,5 s)	
			086	-	097	No function	
			098	-	099	Auto Fan (hold 3s)	
			100	-	101	Fan Off (hold 3s)	
			102	-	103	Fan Constant Low (hold 3s)	
			104	-	105	Fan Constant Medium (hold 3s)	
			106	-	107	Fan Constant High (hold 3s)	
			108	-	119	No function	
			120	-	121	PWM 1 (650 Hz) (hold 3s)	
			122	-	123	PWM 2 (1530 Hz)(hold 3s)	
			124	-	125	PWM 3 (3600 Hz)(hold 3s)	
			126	-	127	PWM 4 (12 kHz)(hold 3s)	
			128	-	129	PWM 5 (18.9 kHz)(hold 3s)	
			130	-	131	PWM 6 (25 kHz)(hold 3s)	
			132	-	133	RAW (hold 3s)	
			134	-	135	Calibrated (hold 3s)	
			136	-	137	User Calibrated (hold 3s)	

S4 IP

LED SOFTLIGHT PANEL - IP65 DMX CONTROL TABLE



16	18	Device Settings (please read remark 1*)	138	-	139	Smart Calibration (hold 3s)	Device Settings
			140	-	141	Display on (hold 3s)	
			142	-	143	Display off (hold 3s)	
			144	-	163	No function	
			164	-	165	Dimmer Curve Linear (hold 3s)	
			166	-	167	Dimmer Curve Exponential (hold 3s)	
			168	-	169	Dimmer Curve Logarithmic (hold 3s)	
			170	-	171	Dimmer Curve S-Curve (hold 3s)	
			172	-	239	No function	
			240	-	241	Default set (except DMX-Address, DMX-Mode) (hold 3s)	
			242	-	243	Default set (except DMX-Address, DMX-Mode and User Colour/Loops) (hold 3s)	
244	-	255	No function				

S4 IP

LED SOFTLIGHT PANEL - IP65
DMX CONTROL TABLE



7 Ch Preset	10Ch HSI-CCT	Function	Values			Sub-Group	
1	1	Dimmer	000	-	255	0% to 100%	Dimmer
2	2	Dimmer fine	000	-	255	0% to 100%	
3	3	Strobe functions	000	-	005	Strobe open	Multifunctional Strobe
			006	-	010	Strobe closed	
			011	-	022	Ramp up/down, slow -> fast	
			023	-	033	Ramp up/down random, slow->fast	
			034	-	045	Ramp up, slow -> fast	
			046	-	056	Ramp up random, slow -> fast	
			057	-	068	Ramp down, slow -> fast	
			069	-	079	Ramp down random, slow -> fast	
			080	-	102	Random Strobe effect, slow -> fast	
			103	-	127	Strobe Break effect, 5s.....1s (short burst with break)	
			128	-	250	Strobe slow -> fast <1Hz - 20Hz	
			251	-	255	Strobe open	
	4	Hue	000	-	255	0° (red) thru 360°	HSI
	5	Saturation	000	-	255	from 0% (white) to 100% pure Colour	
	6	Colour Temperature (affects HSI)	000	-	005	No function	CCT
			006	-	006	Warm white	
			007	-	046	Warm white -> 2700K	
			047	-	047	Bulb White (2700K)	
			048	-	087	2700K -> 3200K	
			088	-	088	Halogen White (3200K)	
			089	-	128	3200K -> 4000K	
			129	-	129	Neutral White (4000K)	
			130	-	169	4000K -> 5600K	
			170	-	170	Studio White (5600K)	
			171	-	210	5600K -> 6500K	
			211	-	211	Daylight White (6500K)	
			212	-	251	6500K -> Cold Daylight	
			252	-	255	Cold Daylight	

S4 IP

LED SOFTLIGHT PANEL - IP65
DMX CONTROL TABLE



	7	Tint (affects Colour Temperature)	000	-	000	Off	Tint
			001	-	127	Magenta -> Neutral	
			128	-	128	neutral	
			129	-	255	Neutral -> Green	

S4 IP

LED SOFTLIGHT PANEL - IP65 DMX CONTROL TABLE



			Lee Filter No.		
4	8	Colour Presets (override Colour Temperature)	000 - 005	no function	Colour Presets
			006 - 009	46 Dark Magenta	
			010 - 013	29 Plasa Red	
			014 - 017	26 Bright Red	
			018 - 021	127 Smokey Pink	
			022 - 025	36 Medium Pink	
			026 - 029	19 Fire	
			030 - 033	135 Deep Golden Amber	
			034 - 037	778 Millennium Gold	
			038 - 041	21 Gold Amber	
			042 - 045	157 Pink	
			046 - 049	110 Middle Rose	
			050 - 053	109 Light Salmon	
			054 - 057	35 Light Pink	
			058 - 061	134 Golden Amber	
			062 - 065	17 Surprise Peach	
			066 - 069	746 Brown	
			070 - 073	105 Orange	
			074 - 077	20 Medium Amber	
			078 - 081	768 Egg Yolk Yellow	
			082 - 085	15 Deep Straw	
			086 - 089	767 Oklahoma Yellow	
			090 - 093	101 Yellow	
			094 - 097	100 Spring Yellow	
			098 - 101	88 Lime Green	
			102 - 105	121 LEE Green	
			106 - 109	738 Jas Green	
			110 - 113	89 Moss Green	
			114 - 117	139 Primary Green	
			118 - 121	124 Dark Green	
			122 - 125	323 Jade	
			126 - 129	354 Special Steel Blue	
			130 - 133	116 Medium Blue-Green	
			134 - 137	183 Moonlight Blue	
138 - 141	132 Medium Blue				
142 - 145	119 Dark Blue				
146 - 149	716 Mikkell Blue				
150 - 153	71 Tokyo Blue				
154 - 157	181 Congo Blue				

S4 IP

LED SOFTLIGHT PANEL - IP65
DMX CONTROL TABLE



Roscolux Filter No.
46
26
50
36
19
22
21
38
331
35
321
17
15
20
15
313
312
10
388
86
4460
89
90
393
370
95
77
74
384
382
382

S4 IP

LED SOFTLIGHT PANEL - IP65 DMX CONTROL TABLE



4	8	Colour Presets (override Colour Temperature)	158 - 161	799 Special KH Lavender	Colour Presets
			162 - 165	707 Ultimate Violet	
			166 - 169	343 Special Medium Lavender	
			170 - 173	798 Chrysalis Pink	
			174 - 177	701 Provence	
			178 - 181	797 Deep Purple	
			182 - 185	48 Rose Purple	
			186 - 189	345 Fuchsia Pink	
			190 - 193	795 Magical Magenta	
			194 - 197	128 Bright Pink	
			198 - 201	2 Rose Pink	
			202 - 207	User Colour_1	
			208 - 213	User Colour_2	
			214 - 219	User Colour_3	
			220 - 225	User Colour_4	
			226 - 231	User Colour_5	
232 - 237	User Colour_6				
238 - 243	User Colour_7				
244 - 249	User Colour_8				
250 - 255	no function				
5	9	Colour Preset Crossfade (Affects Colour Temperature, HSI too)	000 - 005	0s	Light simulation
			006 - 105	0,1s - 10s (0,1s Steps)	
			106 - 214	11s - 119s (1s Steps)	
			215 - 244	2m - 4m50s (10s Steps)	
			245 - 255	5m - 15m (1m Steps)	
6		Effect Macro	000 - 005	No Function	
			006 - 039	Colour Chase	
			040 - 068	Police Car	
			069 - 096	Firetruck	
			097 - 125	Fire	
			126 - 154	Clouds	
			155 - 182	Fireworks	
			183 - 211	Paparazzi	
			212 - 240	Lightning	
241 - 255	No Function				
7		Effect Macro Speed	000 - 255	Effect Macro speed slow --> fast	

S4 IP

LED SOFTLIGHT PANEL - IP65
DMX CONTROL TABLE



382
357
358
358
347
48
346
339
44

S4 IP

LED SOFTLIGHT PANEL - IP65 DMX CONTROL TABLE



			000	-	024	No function	
			025	-	025	Record User Colour 1 (hold 3s)	
			026	-	026	Record User Colour 2 (hold 3s)	
			027	-	027	Record User Colour 3 (hold 3s)	
			028	-	028	Record User Colour 4 (hold 3s)	
			029	-	029	Record User Colour 5 (hold 3s)	
			030	-	030	Record User Colour 6 (hold 3s)	
			031	-	031	Record User Colour 7 (hold 3s)	
			032	-	032	Record User Colour 8 (hold 3s)	
			033	-	073	No function	
			074	-	075	Dimmer Response LED (hold 3s)	
			076	-	077	Dimmer Response Halogen (hold 3s)	
			078	-	081	No function	
			082	-	083	DTW (Redshift) on (hold 1,5 s)	
			084	-	085	DTW (Redshift) off (hold 1,5 s)	
			086	-	097	No function	
			098	-	099	Auto Fan (hold 3s)	
	10	Device Settings (please read remark 1*)					Device Settings

S4 IP

LED SOFTLIGHT PANEL - IP65 DMX CONTROL TABLE



			100	-	101	Fan Off (hold 3s)	
			102	-	103	Fan Constant Low (hold 3s)	
			104	-	105	Fan Constant Medium (hold 3s)	
			106	-	107	Fan Constant High (hold 3s)	
			108	-	119	No function	
			120	-	121	PWM 1 (650 Hz) (hold 3s)	
			122	-	123	PWM 2 (1530 Hz)(hold 3s)	
			124	-	125	PWM 3 (3600 Hz)(hold 3s)	
			126	-	127	PWM 4 (12 kHz)(hold 3s)	
			128	-	129	PWM 5 (18,9 kHz)(hold 3s)	
			130	-	131	PWM 6 (25 kHz)(hold 3s)	
			132	-	133	RAW (hold 3s)	
			134	-	135	Calibrated (hold 3s)	
			136	-	137	User Calibrated (hold 3s)	
			138	-	139	Smart Calibration (hold 3s)	
			140	-	141	Display on (hold 3s)	
			142	-	143	Display off (hold 3s)	
			144	-	163	No function	
			164	-	165	Dimmer Curve Linear (hold 3s)	
			166	-	167	Dimmer Curve Exponential (hold 3s)	
			168	-	169	Dimmer Curve Logarithmic (hold 3s)	
			170	-	171	Dimmer Curve S-Curve (hold 3s)	
			172	-	239	No function	
			240	-	241	Default set (except DMX-Address, DMX-Mode) (hold 3s)	
			242	-	243	Default set (except DMX-Address, DMX-Mode and User Colour/Loops) (hold 3s)	
			244	-	255	No function	
	10	Device Settings (please read remark 1*)					Device Settings

S4 IP

LED SOFTLIGHT PANEL - IP65
DMX CONTROL TABLE



EN: (1*) After the adjustments have been made, set the value to 000 to avoid disturbance by endless function call.

DE: (1*) Nachdem die Einstellungen vorgenommen wurden, stellen Sie den Wert auf 000 ein, um Störungen durch endlosen Funktionsaufruf zu vermeiden.

FR: (1*) Une fois les ajustements effectués, réglez la valeur sur 000 pour éviter les perturbations par appel de fonction sans fin.

ES: (1*) Después de realizar los ajustes, establezca el valor en 000 para evitar perturbaciones mediante una llamada de función sin fin.

PL: (1*) Po dokonaniu ustawień ustaw wartość na 000, aby uniknąć zakłóceń przez niekończące się wywołanie funkcji.

IT: (1*) Dopo aver effettuato le regolazioni, impostare il valore su 000 per evitare disturbi causati da una chiamata a funzione infinita.

32Ch Pixel	Function	Values			
		000	-	255	0% to 100%
1	Red 1	000	-	255	0% to 100%
2	Red 1 fine	000	-	255	0% to 100%
3	Green 1	000	-	255	0% to 100%
4	Green 1 fine	000	-	255	0% to 100%
5	Blue 1	000	-	255	0% to 100%
6	Blue 1 fine	000	-	255	0% to 100%
7	White 1	000	-	255	0% to 100%
8	White 1 fine	000	-	255	0% to 100%
9	Red 2	000	-	255	0% to 100%
10	Red 2 fine	000	-	255	0% to 100%
11	Green 2	000	-	255	0% to 100%
12	Green 2 fine	000	-	255	0% to 100%
13	Blue 2	000	-	255	0% to 100%
14	Blue 2 fine	000	-	255	0% to 100%
15	White 2	000	-	255	0% to 100%
16	White 2 fine	000	-	255	0% to 100%
17	Red 3	000	-	255	0% to 100%
18	Red 3 fine	000	-	255	0% to 100%

S4 IP

LED SOFTLIGHT PANEL - IP65 DMX CONTROL TABLE



19	Green 3	000	-	255	0% to 100%
20	Green 3 fine	000	-	255	0% to 100%
21	Blue 3	000	-	255	0% to 100%
22	Blue 3 fine	000	-	255	0% to 100%
23	White 3	000	-	255	0% to 100%
24	White 3 fine	000	-	255	0% to 100%
25	Red 4	000	-	255	0% to 100%
26	Red 4 fine	000	-	255	0% to 100%
27	Green 4	000	-	255	0% to 100%
28	Green 4 fine	000	-	255	0% to 100%
29	Blue 4	000	-	255	0% to 100%
30	Blue 4 fine	000	-	255	0% to 100%
31	White 4	000	-	255	0% to 100%
32	White 4 fine	000	-	255	0% to 100%